

(주) DH 케미칼

326 Hwasan-ri, Onsan-eub, Ulju-kun, Ulsan 689-896
Republic of Korea
TEL : 82-52-239-2163
FAX : 82-52-239-2151



CERTIFICATE OF ANALYSIS

PRODUCT NAME : Magnatec 5W-30 C3

MANUFACTURED DATE : 28 May 2024

LOT NO : DE2802K

REPORTED DATE : 28 May 2024

<u>ITEM</u>	<u>METHOD</u>	<u>SPECIFICATION</u>	<u>RESULT</u>
APPEARANCE (Conc.)	Visual	Typ.Clear & Bright	Clear & Bright
DENSITY (at 15 °C, g/cm ³)	ASTM D4052	Typ.0.8506	0.8507
Viscosity, Kinematic 100 °C	ASTM D445	10.6 - 12.4	11.83
Viscosity, CCS -30 °C (5W)	ASTM D5293	Max.6600	5727
ZINC (wt%)	ASTM D4951	0.073 - 0.088	0.0769
CALCIUM (wt%)	ASTM D4951	0.078 - 0.092	0.0828
PHOSPHORUS (wt%)	ASTM D4951	0.072 - 0.084	0.0731
FOAM (SEQUENCE II, Tendency)	ASTM D892	Max.20	10
FOAM (SEQUENCE II, Stability)	ASTM D892	Max.0	0
Viscosity, HTHS 150 °C (cP)	ASTM D4683	Min.3.45	3.48

위 시험은 비피코리아(주)의 면허하에 생산된 제품을 (주)DH케미칼의 품질보증시스템에 의거하여 수행하였으며,
그 시험결과는 틀림이 없으며 규격을 만족합니다. 또한 이 문서는 컴퓨터로 처리되어 직인을 생략합니다.

K.H.Choi
R&D Manager